

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1	(system adj indentification) and (point adj model) and linear	USPAT	OR	ON	2005/01/13 10:11
L2	1	(system adj indentification) and (point adj model) and linear	USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/01/13 10:12
L3	837	(703/2).CCLS.	USPAT	OR	OFF	2005/01/13 10:12
L4	17	3 and (system adj indentification)	USPAT	OR	OFF	2005/01/13 10:12
L5	17	3 and (system adj indentification)	USPAT	OR	ON	2005/01/13 10:21
L6	2345	((703/2) or (703/6) or (700/44) or (700/45) or (700/28) or (700/29) or (700/33) or (700/30)).CCLS.	USPAT	OR	OFF	2005/01/13 10:22
L7	89	6 and (system adj indentification)	USPAT	OR	ON	2005/01/13 10:22
L8	5	7 and (point adj model)	USPAT	OR	ON	2005/01/13 10:22

**Welcome to IEEE Xplore®**

- ☐ Home
- ☐ What Can I Access?
- ☐ Log-out

**Tables of Contents**

- ☐ Journals & Magazines
- ☐ Conference Proceedings
- ☐ Standards

**Search**


- ☐ By Author
- ☐ Basic
- ☐ Advanced
- ☐ CrossRef

**Member Services**

- ☐ Join IEEE
- ☐ Establish IEEE Web Account
- ☐ Access the IEEE Member Digital Library

**IEEE Enterprise**

- ☐ Access the IEEE Enterprise File Cabinet



Print Format

Your search matched **1** of **1112315** documents.

A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance** in **Descending** order.

**Refine This Search:**

You may refine your search by editing the current search expression or entering a new one in the text box.

'point model' <and> 'system identification'

**Search**

☐ Check to search within this result set

**Results Key:**

**JNL** = Journal or Magazine   **CNF** = Conference   **STD** = Standard

**1 Turbine system identification: experimental results**


*Mehta, A.; Kaufman, H.; Ravi, R.;*

Decision and Control, 1994., Proceedings of the 33rd IEEE Conference on , Volume: 4 , 14-16 Dec. 1994

Pages:3593 - 3595 vol.4



[\[Abstract\]](#)   [\[PDF Full-Text \(188 KB\)\]](#)   **IEEE CNF**

## THE ACM DIGITAL LIBRARY

 [Feedback](#) [Report a problem](#) [Satisfaction survey](#)

Terms used **point model** and **system identification**

Found **191** of **148,786**


Sort results by    
 Display results    
☒ Save results to a Binder  
☒ Search Tips  
☐ Open results in a new window


Try an [Advanced Search](#)  
 Try this search in [The ACM Guide](#)

Results 1 - 20 of 191


Result page: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [next](#)

Relevance scale ☐ ☐ ☐ ☐ ☐

- 1 [PDEL-ID: An extension of PDEL for distributed parameter system identification](#)   
 Wing Cheung Tam, Walter J. Karplus  
 March 1974 **Proceedings of the ACM SIGPLAN symposium on Very high level languages**


Full text available:  [pdf\(584.68 KB\)](#) Additional Information: [full citation](#), [abstract](#), [references](#), [citations](#), [index terms](#)

Mathematical models have been commonly used for the simulation of continuous time systems on a digital computer. In many cases, the system models involve parameters which have to be identified from observed data. The digital simulation language PDEL was extended to provide the facilities and capabilities for the identification of parameters in distributed parameter systems. The extended program is designated as PDEL-ID. The extension includes new language statements and convenient facilities ...

- 2 [Topics in timing: A library compatible driving point model for on-chip RLC interconnects](#)   
 Kanak Agarwal, Dennis Sylvester, David Blaauw  
 December 2002 **Proceedings of the 8th ACM/IEEE international workshop on Timing issues in the specification and synthesis of digital systems**

Full text available:  [pdf\(243.94 KB\)](#) Additional Information: [full citation](#), [abstract](#), [references](#), [index terms](#)

This paper presents a new library compatible approach to gate-level timing characterization in the presence of RLC interconnect loads. We describe a two-ramp model based on transmission line theory that accurately predicts both the 50% delay and waveform shape (slew rate) at the driver output when inductive effects are significant. The approach does not rely on piecewise linear Thevenin voltage sources. It is compatible with existing library characterization methods and is computationally efficient ...

- 3 [System identification using frequency domain methodology](#)   
 Arnold Buss  
 December 1990 **Proceedings of the 22nd conference on Winter simulation**

Full text available:  [pdf\(383.12 KB\)](#) Additional Information: [full citation](#), [references](#), [citations](#), [index terms](#)

- 4 [Hybrid aspects for weaving object-oriented functionality and rule-based knowledge](#)   
 Maja D'Hondt, Viviane Jonckers  
 March 2004 **Proceedings of the 3rd international conference on Aspect-oriented software development**

Full text available:  [pdf\(989.52 KB\)](#) Additional Information: [full citation](#), [abstract](#), [references](#)

Software applications often consist of implicit knowledge for making decisions or giving advice in addition to object-oriented functionality. A rule-based system can be employed for representing and reasoning with this knowledge. Although several hybrid systems exist that combine object-oriented programming and rule-based reasoning, a survey we conducted reveals that both paradigms are not well integrated and programs are tightly coupled. We